

SPECIFICATIONS

SZ0603 TYPE

Part Number	Impedance	Z Test Frequency	Max. DC Resistance	Max. Rated Current	Thickness
Units	Ω	MHz	Ω	mA	mm [inch]
Symbol	Z	Freq.	DCR	I _r	T
SZ0603G100TF	10 $\pm$ 25%	100	0.25	200	0.3 $\pm$ 0.05 [.012 $\pm$.002]
SZ0603G220TF	22 $\pm$ 25%	100	0.45	200	
SZ0603G330TF	33 $\pm$ 25%	100	0.55	150	
SZ0603G470TF	47 $\pm$ 25%	100	0.70	150	
SZ0603G560TF	56 $\pm$ 25%	100	1.00	100	

SZ1005 TYPE

Part Number	Impedance	Z Test Frequency	Max. DC Resistance	Max. Rated Current	Thickness
Units 单位	Ω	MHz	Ω	mA	mm [inch]
Symbol 符号	Z	Freq.	DCR	I _r	T
SZ1005F050TF	0~10	100	0.10	300	0.5 $\pm$ 0.15 [.020 $\pm$.006]
SZ1005F100TF	5~15	100	0.20	300	
SZ1005F330TF	33 $\pm$ 25%	100	0.40	300	
SZ1005F470TF	47 $\pm$ 25%	100	0.60	200	
SZ1005F560TF	56 $\pm$ 25%	100	0.80	200	
SZ1005G050TF	0~15	100	0.15	600	
SZ1005G300TF	30 $\pm$ 25%	100	0.15	600	
SZ1005G750TF	75 $\pm$ 25%	100	0.30	600	
SZ1005G121TF	120 $\pm$ 25%	100	0.40	400	
SZ1005G221TF	220 $\pm$ 25%	100	0.70	200	
SZ1005K750TF	75 $\pm$ 25%	100	0.30	600	
SZ1005K121TF	120 $\pm$ 25%	100	0.40	400	
SZ1005K221TF	220 $\pm$ 25%	100	0.70	200	
SZ1005K301TF	300 $\pm$ 25%	100	0.80	200	
SZ1005K421TF	420 $\pm$ 25%	100	1.00	150	
SZ1005K601TF	600 $\pm$ 25%	100	1.10	100	
SZ1005K102TF	1000 $\pm$ 25%	100	1.20	100	
SZ1005K152TF	1500 $\pm$ 25%	100	1.40	100	
SZ1005K182TF	1800 $\pm$ 25%	100	1.80	50	

SZ1608 TYPE

Part Number	Impedance	Z Test Frequency	Max. DC Resistance	Max. Rated Current	Thickness
Units	Ω	MHz	Ω	mA	mm [inch]
Symbol	Z	Freq.	DCR	I _r	T
SZ1608F050TF	0~10	100	0.20	500	0.8 $\pm$ 0.15 [.031 $\pm$.006]
SZ1608F100TF	5~15	100	0.25	500	
SZ1608F220TF	22 $\pm$ 25%	100	0.35	500	
SZ1608F470TF	47 $\pm$ 25%	100	0.55	300	
SZ1608F750TF	75 $\pm$ 25%	100	0.70	300	
SZ1608F121TF	120 $\pm$ 25%	100	0.90	200	
SZ1608G050TF	0~15	100	0.10	800	
SZ1608G220TF	22 $\pm$ 25%	100	0.20	800	
SZ1608G600TF	60 $\pm$ 25%	100	0.30	600	
SZ1608G121TF	120 $\pm$ 25%	100	0.45	600	
SZ1608G221TF	220 $\pm$ 25%	100	0.55	500	
SZ1608G331TF	330 $\pm$ 25%	100	0.70	500	
SZ1608G471TF	470 $\pm$ 25%	100	0.80	400	
SZ1608G601TF	600 $\pm$ 25%	100	1.10	200	
SZ1608G102TF	1000 $\pm$ 25%	100	1.20	150	
SZ1608K121TF	120 $\pm$ 25%	100	0.40	600	

SPECIFICATIONS

SZ1608 TYPE

Part Number	Impedance	Z Test Frequency	Max. DC Resistance	Max. Rated Current	Thickness
Units	Ω	MHz	Ω	mA	mm [inch]
Symbol	Z	Freq.	DCR	I _r	T
SZ1608K221TF	220±25%	100	0.45	500	0.8±0.15 [.031±.006]
SZ1608K331TF	330±25%	100	0.50	500	
SZ1608K421TF	420±25%	100	0.55	400	
SZ1608K471TF	470±25%	100	0.55	400	
SZ1608K601TF	600±25%	100	0.60	200	
SZ1608K102TF	1000±25%	100	0.80	200	
SZ1608K152TF	1500±25%	100	0.80	200	
SZ1608K202TF	2000±25%	100	1.00	200	
SZ1608K222TF	2200±25%	100	1.00	200	
SZ1608K252TF	2500±25%	100	1.20	200	
SZ1608K272TF	2700±25%	100	1.40	200	


SZ2012 TYPE

Part Number	Impedance	Z Test Frequency	Max. DC Resistance	Max. Rated Current	Thickness
Units	Ω	MHz	Ω	mA	mm [inch]
Symbol	Z	Freq.	DCR	I _r	T
SZ2012G050TF	0~15	100	0.07	1000	0.85±0.2 [.033±.008]
SZ2012G300TF	30±25%	100	0.10	1000	
SZ2012G600TF	60±25%	100	0.20	800	
SZ2012G121TF	120±25%	100	0.25	600	
SZ2012G221TF	220±25%	100	0.30	600	
SZ2012G421TF	420±25%	100	0.40	600	
SZ2012G601TF	600±25%	100	0.45	600	
SZ2012G102TF	1000±25%	100	0.50	500	
SZ2012K121TF	120±25%	100	0.20	600	
SZ2012K221TF	220±25%	100	0.25	600	
SZ2012K301TF	300±25%	100	0.30	600	
SZ2012K421TF	420±25%	100	0.30	600	
SZ2012K601TF	600±25%	100	0.35	600	
SZ2012K102TF	1000±25%	100	0.40	500	
SZ2012K152TF	1500±25%	100	0.45	200	
SZ2012K222TF	2200±25%	100	0.60	200	
SZ2012K252TF	2500±25%	100	0.70	200	
SZ2012K272TF	2700±25%	100	0.80	200	

※: Products with other electrical characteristics can be provided upon customer's request. Please contact your local sales.

TYPICAL ELECTRICAL CHARACTERISTICS

F, G, K Material Comparison








Sunlord

Specifications subject to change without notice. Please check our website for latest information. Revised 2013/05/15













Sunlord Industrial Park, Dafuyuan Industrial Zone, Guanlan, Shenzhen, China 518110 Tel: 0086-755-29832660 Fax: 0086-755-82269029 E-Mail: sunlord@sunlordinc.com

DETAIL ELECTRICAL CHARACTERISTICS

SZ0603 TYPE



SZ1005 TYPE










Sunlord

Specifications subject to change without notice. Please check our website for latest information. Revised 2013/05/15










Sunlord Industrial Park, Dafuyuan Industrial Zone, Guanlan, Shenzhen, China 518110 Tel: 0086-755-29832660 Fax: 0086-755-82269029 E-Mail: sunlord@sunlordinc.com

DETAIL ELECTRICAL CHARACTERISTICS

SZ1005 TYPE



SZ1608 TYPE





















Sunlord

Specifications subject to change without notice. Please check our website for latest information. Revised 2013/05/15

Sunlord Industrial Park, Dafuyuan Industrial Zone, Guanlan, Shenzhen, China 518110 Tel: 0086-755-29832660 Fax: 0086-755-82269029 E-Mail: sunlord@sunlordinc.com

DETAIL ELECTRICAL CHARACTERISTICS

SZ1608 TYPE





















Sunlord

Specifications subject to change without notice. Please check our website for latest information. Revised 2013/05/15

Sunlord Industrial Park, Dafuyuan Industrial Zone, Guanlan, Shenzhen, China 518110 Tel: 0086-755-29832660 Fax: 0086-755-82269029 E-Mail: sunlord@sunlordinc.com

DETAIL ELECTRICAL CHARACTERISTICS

SZ2012 TYPE



Sunlord

Specifications subject to change without notice. Please check our website for latest information. Revised 2013/05/15

Sunlord Industrial Park, Dafuyuan Industrial Zone, Guanlan, Shenzhen, China 518110 Tel: 0086-755-29832660 Fax: 0086-755-82269029 E-Mail: sunlord@sunlordinc.com